

Model**GTBZ20****Dimensions**

Platform height	67 ft 6 in (20.6 m)
Working height	74 ft 1 in (22.6 m)
Horizontal outreach	56 ft 8 in (17.3 m)
Length (stowed)	30 ft 1 in (9.18 m)
Width (stowed)	8 ft 2 in (2.49 m)
Height (stowed)	9 ft 2 in (2.8 m)
Ground clearance	1 ft 5 in (0.45 m)
Wheel base	8 ft 2 in (2.49 m)
Size of platform (L*W*H)	4 ft 8 in * 2 ft 8 in * 4 ft 1 in (1.45 m * 0.85 m * 1.24 m)

Performance Data

Platform Capacity	2
Load capacity of platform	1060 lbs (480 kg)
Turntable rotation	360°
Platform rotation	160°
Driving speed (stowed)	0~4 mph (6.3 km/h)
Driving speed (raised)	0~0.7 mph (1.1 km/h)
Gradeability	30% (2WD) 45% (4WD)
Outside turning radius	16 ft 3 in (4.97 m)
Inside turning radius	5 ft 4 in (1.66 m)
Tail swing	4 ft 3 in (1.32 m)
Allowable slope	3°
Drive * steering	2 WD * 2 WS / 4 WD * 2 WS
Tire size/type	9.00 - 20 / Solid

Engine

Power source	diesel engine
Drive Type	Hydraulic pressure
Volume of hydraulic oil tank	160 L
Power	45 KW

Weight

Overall weight	24284 lbs(11015 kg) - (2WD)
	24438 lbs(11085 kg) - (4WD)

Standards compliant CE, ISO, GOST