




JCPT(CRT)

Self-Propelled Rough-Terrain Scissor Lifts

JCPT1017RT / JCPT1217RT / JCPT1417RT

	JCPT1017RT	JCPT1217RT	JCPT1417RT
S.W.L	567kg	454kg	345kg
S.W.L on extension	136kg	136kg	136kg
Max. Occupants	4	4	3
Working height	10.0m	12.0m	14.0m
Platform floor height	8.0m	10.0m	12.0m
Overall length(with/without outriggers)	3.30m/2.67m	3.30m/2.67m	3.30m/2.67m
Overall width	1.73m	1.73m	1.73m
Overall height(standard/olded guardrails)	2.42m/1.82m	2.55m/1.95m	2.68m/2.08m
Platform size	2.51X1.55m	2.51X1.55m	2.51X1.55m
Platform extension size	1.43m	1.43m	1.43m
Ground clearance	0.19m	0.19m	0.19m
Wheelbase	1.85m	1.85m	1.85m
Turning radius(inside/Outside)	2.00m/3.90m	2.00m/3.90m	2.00m/3.90m
Engine	Kubota D1105 18.6kw/2400 rpm		
Travel speed(Stowed)	6.1 km/h	6.1 km/h	6.1 km/h
Travel speed(Raised)	1.1 km/h	1.1 km/h	1.1 km/h
Up/Down speed	41/48 sec	40/37 sec	50/40 sec
Gradeability	35%	30%	30%
Maximum working slope	3-5°	3-5°	3-5°
Hydraulic tank	62L	62L	62L
Diesel tank	55L	55L	55L
Tyres	26X12-16.5	26X12-16.5	26X12-16.5
Weight(with/without outriggers)	3600kg/3280kg	3830kg/3550kg	3980kg/3750kg



Swing-out engine tray



Standard equipment

- Proportional controls
- Self-lock gate on platform
- Drivable at full height
- Foam filled tyre
- 4WD
- Automatic brake system
- Swing-out engine tray
- Emergency lowering system
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- Anti-restart engine protection
- All Motion Alarm
- Horn
- Hour meter
- Safety brackets
- Folding guardrails
- Extended platform
- European III emission engine
- Flashing Beacon
- Hydraulic oil cooler

Options

- Overload sensor with alarm
- Automatic leveling hydraulic outriggers
- AC power to platform
- Platform work lights
- Airline to platform
- Hydraulic generator
- Non-marking tyre



Automatic leveling outriggers Non marking tyre



Waterproof Safety bar Folding guardrails Brake release valve Gradeability